

# AYDINDISPLAYS

a sparton company

WWW.SPARTONRE.COM | SALES@SPARTONRE.COM



## MODEL 4424S

*24" RACK/CONSOLE MOUNT  
COLOR FLAT PANEL DISPLAY*

### FEATURES:

- Ultra Resolution, 1920 x 1200
- Anti-Reflective Protective Window
- Convenient Front Controls

### OPTIONS:

- Touchscreen
- Flicker Compensation for Display of Sonar Acoustic Data

Aydin is:



7/18\_REV. 1

# SPECIFICATIONS:

**Active Display Area:** 518.4 x 324.0 mm  
(20.41" x 12.96")

**Pixel Pitch:** 0.270 x 0.270 mm

**Brightness:** 250 cd/m<sup>2</sup> (Typical)

**Viewing Angle:** ±89° All Directions (Typical)

**Contrast Ratio:** 1000:1 (Typical)

**Response Time:** 16 ms Tr + Tf (Typical)  
6 ms GtG (Typical)

**Display Colors:** 16 Million

**Input Signal:** **Analog video:**  
**Video Sync:** Analog 0.7 V p-p/75 Ω Separate sync. TTL level  
**Horizontal Sync:** Positive/Negative  
**Vertical Sync:** Positive/Negative  
**Composite Sync:** Positive/Negative Sync on Green (Video 0.7p-p and Sync 0.3Vp-p)

**Input Interface:** VGA (HD15F), DVI-D (DVI Connector)

**Video Input Impedance:** 75 Ohms

**Resolutions Supported:**  
640 x 480 @ 60 Hz  
720 x 400 @ 85 Hz  
800 x 600 @ 60 Hz  
1024 x 768 @ 60 Hz  
1280 x 1024 @ 60 Hz  
1600 x 1200 @ 60 Hz

**Native Resolution:** 1920 x 1200 @ 60 Hz

**Display Controls:** Power, Brightness, OSD

**Remote Control:** RS232 Interface for Control of Adjustments

**Temperature:** **Operating:** (Sea Level): 0 °C to 50 °C, MIL-STD-810E Method 501.3/502.3, Procedure II  
**Storage:** -20 °C to + 60 °C, MIL-STD-810E, Method 501.3/502.3, Procedure 1

**Humidity:** **Operating/Storage:** 5 to 95% RH, Non-condensing, MIL STD-810E, Method 507.3

**Altitude:** **Operating:** 0 to 15,000 ft. above sea level  
**Storage:** 0 to 50,000 ft. above sea level (MIL-STD 810E, Method 500.3)

**Shock:** MIL-S-901D, Grade A, Class I, Type A

**Vibration:** MIL-STD-167-1, Type I

**Drip:** MIL-STD-810E, Method 506.3, Procedure II, Front Panel Only

**Sand/Dust:** MIL-STD-810E, Method 510.3 Front Panel Only

**EMI:** MIL-STD-461E, CE102, CS101, CS114, CS116, RE102, RS101, RS103

**Power:** **Supply:** Internal 88-264/ VAC Auto Ranging  
**Frequency:** 43-63Hz  
**Power:** 104 Watts (Typical)  
**Chassis Connector:** MS3102A-10SL-3P  
**Cable Connector:** MS3106A-10SL-3S

**Dimensions:** 24"W x 15.72"H x 4.5" DP

**Weight:** 25 lbs