

## Model CFP21W2-1G0-D0A 21.3" VESA Mount Sunlight Readable Display

21.3" 1600 X 1200 ACTIVE MATRIX LCD (AMLCD) WITH LED BACKLIGHT  
 760 NITS SUNLIGHT READABLE  
 CONTRAST RATIO IS 24:1 @ 6000 fL WITH BONDED AR/AG WINDOW  
 WIDE VIEWING ANGLE ± 88° (ALL DIRECTIONS)  
 DEEP DIMMING  
 AUTO RANGING AC POWER SUPPLY  
 RUGGED CONSTRUCTION  
 100/200 mm VESA MOUNT WITH STAND



<b>Display Type:</b>	21.3" TFT
<b>Active Display Area:</b>	17.01"(w) x 12.76"(h) (432 x 324 mm)
<b>Pixel Pitch:</b>	.27 mm
<b>Brightness:</b>	760 Nits LED Backlight
<b>Viewing Angle:</b>	Left/ Right 88°/88° Up/ Down 88°/88°
<b>Contrast Ratio:</b>	24:1 @ 6000 fL
<b>Response Time:</b>	40 ms White to Black
<b>Display Colors:</b>	16.7M
<b>Input Signal: Video:</b>	Analog 0.7V p-p/75 Ω
<b>Sync:</b>	Separate H&V, Combined, SOG
<b>Input Interface:</b>	RCA, Mini-DIN, HD-15, DVI-D
<b>Video Inputs:</b>	NTSC/PAL (RCA) Mini-DIN (S-Video) VGA DVI-D
<b>Resolutions Supported:</b>	640 x 480 800 x 600 1024 x 768 1280 x 1024 1600 x 1200
<b>Native Resolutions:</b>	1600 x 1200 (UXGA)

<b>Temperature:</b>	Operating:	0°C to 50°C
	Storage:	-20°C to +60°C
<b>Humidity (Non-Condensing):</b>	Operating:	10 to 95%
	Storage:	10 to 95%
<b>Altitude:</b>	Operating:	0 to 10,000 ft.
	Storage:	0 to 40,000 ft.
<b>Shock:</b>	30g's, 11ms, ½ Sine	
<b>Vibration:</b>	1g RMS 20-500Hz	
<b>Power Requirements:</b>	Power Supply:	90-264 VAC Auto Switching @ 50/60 Hz (Internal)
	Power/ Current:	55 Watts (Max) .52a
<b>Dimensions &amp; Weight:</b>	Height:	15.02" (381.51 mm)
	Width:	19.27" (489.46 mm)
	Depth:	3.8" (96.52 mm)

